



# 3M™ DBI-SALA® Delta™ Comfort Harness

The newest Delta Comfort full-body harness offers innovative features such as an improved ergonomic fit and feel, lighter-weight buckles and high-strength webbing. Employing a patented No-Tangle triangle pattern creates a frame that allows the harness to easily fall into place when donned. The Delta Comfort harness features liquid-resistant 3M™ DBI-SALA® Delta™ Repel™ Technology Webbing and 3M™ DBI-SALA® Revolver™ Torso Adjusters, which allow for quick adjustment and eradicates loose strap ends.

## Applications



### 3M™ DBI-SALA® Repel™ Technology Webbing

Water repellent to reduce attraction of mould and dirt - also has up to 5 times more resistance to abrasion.

### Gear Loops and Connectors

Range of connection and storage points for tools and pouches.

### Comfort Padding

To the underside of the shoulder straps, hips and legs.

### 3M™ DBI-SALA® Revolver™ Torso Adjusters

These innovative adjusters have patent pending. Simple and fast adjustment that eliminates loose ends and locks into place preventing slippage.

### 3M™ DBI-SALA® Tech-Lite™ Quick Connect Buckles

Lightweight aluminium alloy buckles for fast and easy connections. Other connections available (Pass Through models also available).

### Stand Up Dorsal D-ring

Stands-up dorsal D-ring, ensures fast, easy and safe connections to your fall arrest system.

### Rigid Belt

Allows for 27 kg of tools without collapsing.

### Protected Labels

A Velcro® cover protects harness labels.

### Weight Capacity

140 kg.



### 3M™ DBI-SALA® Delta™ Comfort Harness



	↔	🔗	🌀	📊
1112956	S	PT	PT	1.40
1112955	U	PT	PT	1.45
1112957	XL	PT	PT	1.55

### Delta Comfort Harness with Quick Connect Buckles



	↔	🔗	🌀	📊
1112959	S	QC	QC	1.60
1112958	U	QC	QC	1.65
1112960	XL	QC	QC	1.75

### 3M™ DBI-SALA® Delta™ Comfort Harness with Belt



	↔	🔗	🌀	🌀	📊
1112962	S	PT	PT	PT	2.35
1112961	U	PT	PT	PT	2.40

### Delta Comfort Harness with Belt & Quick Connect Buckles



	↔	🔗	🌀	🌀	📊
1112965	S	QC	QC	QC	2.55
1112964	U	QC	QC	QC	2.60
1112966	XL	QC	QC	QC	2.70

### Delta Comfort Harness



	↔	🔗	🌀	📊
1112947	S	PT	PT	1.50
1112946	U	PT	PT	1.55
1112948	XL	PT	PT	1.65

### Delta Comfort Harness with Quick Connect Buckles



	↔	🔗	🌀	📊
1112953	S	QC	QC	1.70
1112952	U	QC	QC	1.75
1112954	XL	QC	QC	1.85

Best Seller  
1112952

### Delta Comfort Rescue Harness with Belt



	↔	🔗	🌀	📊
1112950	S	PT	PT	1.70
1112949	U	PT	PT	1.75
1112951	XL	PT	PT	1.85

### 3M™ DBI-SALA® Work Positioning Spreader Bar Lanyard



	↔	🔗	🌀	🌀	📊
KF71201466	45 mm	🔗	19 mm	Ⓢ	1.30

Confined space lanyard for use with rescue harness incorporating shoulder D-rings. Use for vertical lifts in confined space or rescue situations. Built in spreader bar keeps shoulder straps from being pulled in during use.



# 3M™ DBI-SALA® Delta™ Harness

Innovative body support for more than two decades.

Toughness. Versatility. These are qualities expected of you, so you should expect nothing less from your safety harness. Delta harnesses combine a number of innovations with popular features that have made an industry workhorse that's as tough as those who wear them. Delta harnesses have a shape of their own, so you can down them quickly and easily.

### Applications



### 3M™ DBI-SALA® Delta™ Repel™ Technology Webbing

Water repellent to reduce attraction of mould and dirt - also has up to 5 times more abrasion resistance.

### Lanyard Keepers

Avoids carrying lanyard by hand when no longer in use.

### Revolver™ Vertical Torso Adjusters

Simple and fast adjustments that eliminate loose ends and lock into place, preventing slippage.

### Covered Labels

A Velcro® cover protects harness labels.

### Built-in Impact Indicators

Rip-stitch indicators allow you to inspect the harness at a glance, for prior damaging impact loads.

### Stand Up Dorsal D-ring

Patented spring-loaded design automatically stands-up, ensuring fast, easy and safe connections to your fall arrest system.

### 3M™ DBI-SALA® No-Tangle™ Design

Defining the Delta name, the patented triangular design creates a frame that allows the harness to fall into place when donned.

### 3M™ DBI-SALA® Surefit™ No-Tangle Design

Ensures correct fitting of the harness in the event of a fall while still providing additional comfort for everyday use.

### Weight Capacity

140 kg.



3M™ DBI-SALA® Delta™ Harness



	↔	🔗	🔗	📊
1112916	S	PT	PT	1.40
1112915	U	PT	PT	1.44
1112917	XL	PT	PT	1.55

Delta Harness with Quick Connect Buckles



	↔	🔗	🔗	📊
1112919	S	QC	QC	1.60
1112918	U	QC	QC	1.65
1112920	XL	QC	QC	1.75

3M™ DBI-SALA® Delta™ Harness with Belt



	↔	🔗	🔗	🔗	📊
1112907	S	PT	PT	PT	2.35
1112906	U	PT	PT	PT	2.40
1112908	XL	PT	PT	PT	2.50

Delta Harness with Belt & Quick Connect Buckles



	↔	🔗	🔗	🔗	📊
1112910	S	QC	QC	QC	2.55
1112909	U	QC	QC	QC	2.60
1112911	XL	QC	QC	QC	2.70

Delta Harness



	↔	🔗	🔗	📊
1112901	S	PT	PT	1.50
1112900	U	PT	PT	1.55
1112902	XL	PT	PT	1.65

Delta Harness with Quick Connect Buckles



Best Seller  
1112912

	↔	🔗	🔗	📊
1112913	S	QC	QC	1.70
1112912	U	QC	QC	1.75
1112914	XL	QC	QC	1.85

Delta Harness with Belt



	↔	🔗	🔗	🔗	📊
1112922	S	PT	PT	PT	2.35
1112921	U	PT	PT	PT	2.40
1112923	XL	PT	PT	PT	2.50

Delta Harness with Belt & Quick Connect Buckles



	↔	🔗	🔗	🔗	📊
1112925	S	QC	QC	QC	1.75
1112924	U	QC	QC	QC	2.55
1112926	XL	QC	QC	QC	2.70



# 3M™ DBI-SALA® Delta™ Nomex® Kevlar® Webbing Harness

**Applications**



The 3M™ DBI-SALA® Delta™ Harness high temperature is constructed from webbing with a Nomex outer and a Kevlar core. The webbing has a 425°C char temperature resistance level. This innovative webbing is as flexible and soft to the touch as any traditional webbing. The harness also incorporates the 3M™ DBI-SALA® Delta™ No-Tangle™ triangular frame that allows the harness to easily fall into place when donned and increases comfort during use. Also incorporates covered labels.



## 3M™ DBI-SALA® Delta™ Nomex® Kevlar® Webbing Harness



	↔	🔗	🔗	📊 kg
KB1K-P29	M	PT	PT	1.45

## Delta Nomex Kevlar Webbing Harness



Best Seller  
1101714

	↔	🔗	🔗	📊 kg
1101714	U	PT	PT	1.71
1101718	XL	PT	PT	1.91

## Delta Nomex Kevlar Webbing Welders Harness



	↔	🔗	🔗	📊 kg
1191552	S/M	CC	CC	1.50
1191553	M/L	CC	CC	1.55
1191554	XL	CC	CC	1.60



For 3M™ DBI-SALA®  
Nano-Lok™ Hot Work  
SRL's see page 86

## 3M™ DBI-SALA® Suspension Trauma Safety Straps - Fire Resistant



	📊 kg
9505712	0.14

Suspension trauma safety straps, one pair, fire resistant, attaches to most harnesses.