

Model FP-700

Combustible Gas Sensor



Scrolling Full Message/Text Display



Matched Pair Catalytic Bead
(shown as PN 967-524520-100 in SS junction box)



Features

Failsafe User-Friendly Interface

- LED Display (With Antiglare Cover)
- Full Text Display Method
- Non-intrusive Interface
- Auto Zero/Auto Span
- Pre-emptive Fault Diagnostics

Environmentally Bulletproof

- Electropolished 316SS Construction
- 100% Epoxy Encapsulated Circuitry
- Bulletproof I/O Protection
- Water-Proof, Corrosion-Proof, Vibration-Proof

Modular and Serviceable

- Modular Design
- Plug and Play Components
- Quick Thread Release (For Sensor Replacement)
- Integral Calibration Port

Description

Model FP-700 is a non-intrusive “Smart” sensor designed to detect and monitor combustible gases in air over the range of 0-100% LEL using catalytic bead sensor technology. The plug-in, field replaceable detector is poison-resistant and features over-sized gold-plated connections that help prevent corrosion. The FP-700’s rugged framework includes an electro-polished 316 stainless steel housing with fully encapsulated electronics and dual layer surge protection. This innovative design virtually eliminates sensor failure due to water ingress, corrosion, vibration, and transient spikes. A primary feature of the Model FP-700 is embedded intuitive software that simplifies operator interface by guiding the user through routine calibration, configuration, and fault diagnostic functions using a built-in alpha/numeric display. The Model FP-700 is equipped with standard analog 4-20mA, and Modbus™ RS-485 outputs. Among its unique features is a wireless option that can be used with Detcon’s SmartWireless® product line. Additional integration options include a Remote Alarm Module (RAM), and HART. Detcon’s combustible gas sensor has an infinite shelf life and is supported by a 2-year warranty.

Applications

- Oil and Gas Drilling Rigs
- Oil and Gas Production Sites
- Offshore Production Platforms
- FPSOs
- LNG/CNG Plants
- Refining and Petrochemical
- Pulp and Paper Mills
- Waste Water Treatment Plants



Model Model FP-700

Combustible Gas Sensor

System Specifications

Sensor Type

Continuous diffusion/adsorption
Matched-pair catalytic bead detector
Plug-in field replaceable

Sensor Life

3 to 5 years typical

Measurement Range

0-100% LEL (lower explosive limit)

Accuracy/Repeatability

±3% 0-50% LEL; ±5% 50-100% LEL

Response/Clearing Time

T50 <10 seconds; T90 <30 seconds

Zero Drift

<5% per year

Outputs

Linear 4-20 mA DC
RS-485 MODBUS-RTU

Electrical Classification

Explosion proof
cCSAus
Class I, Division 1, Groups B, C, D (Tamb = -40°C to +75°C)
Class I, Zone 1, Group IIB+H2
ATEX
II 2 G Ex d IIB + H2 T4 Gb (Tamb = -40°C to +70°C)

Ingress Protection

NEMA 4X, IP66

Safety Approvals

cCSus Performance to ANSI/ISA 60079-29-1
(12.13.01)-2013 and CSA 22.2 #152
ATEX
CE Marking
SIL2 Certified to IEC 61508

Warranty

Plug-in detector - 2 years
Transmitter - 2 Years

Environmental Specifications

Operating Temperature Range

-40°F to +167°F; -40°C to +75°C

Storage Temperature Range

-40°F to +167°F; -40°C to +75°C

Operating Humidity Range

0-99% RH non-condensing

Specifications subject to change without notice

Order Guide

Specify junction box options (below)

PN 967-525520-100 FP-700 Sensor Assembly (no junction box)
PN 967-521520-100 FP-700 Sensor Assembly with Aluminum Junction Box
PN 967-524520-100 FP-700 Sensor Assembly with 316 SS Junction Box
PN 9H7-521520-100 FP-700 Sensor Assembly with HART in Aluminum Junction Box
PN 9H7-524520-100 FP-700 Sensor Assembly with HART in 316 SS Junction Box
PN 9R7-524520-100 FP-700 Sensor Assembly with RAM in Aluminum Junction Box
PN 9R7-524520-100 FP-700 Sensor Assembly with HART in 316SS Junction Box

Mechanical Specifications

Dimensions

7"H x 2.2" Dia.; 178mmH x 65mm Dia.
(sensor assembly only)
11"H x 6.1"W x 3.75"D; 280mmH x 155mmW x 96mmD
(with junction box)
Mounting holes (J-box) 5.5"; 140mm center to center

Weight

2 lbs; 0.907kg (sensor only)
6 lbs; 2.72kg (w/aluminum j-box)
9 lbs; 4.08kg (w/stainless steel j-box)

Electrical Specifications

Power Input

11-30 VDC

Power Consumption

Normal operation = 68mA (<1.7 watt)
Maximum = 85mA (2 watts)

Inrush Current

1.0A @ 24V

RFI/EMI Protection

Complies with EN50270

Analog Output

Linear 4-20mA DC (1,000 ohms max loop load @ 24VDC)
0mA All Fault Diagnostics
2mA In-Calibration
4-20mA 0-100% full-scale
22mA Over-range condition

Serial RS-485 Output

RS-485 Modbus™ RTU

Baud Rate

9600 BPS (9600,N,8,1 Half Duplex)

Status Indicators

4-digit LED display with gas concentration
Full-script menu prompts for AutoSpan,
Set-up Options, and Fault Reporting

Faults Monitored

Operating Temperature, Loop, Input Voltage,
Bridge Voltage, Zero, Sensor,
Processor, Memory, Calibration

Cable Requirements

Power/Analog
3-wire shielded cable
Maximum distance is 13,300 feet with 14 AWG
Serial Output
2-wire twisted-pair shielded cable specifically for
use with RS-485 installations
Maximum distance is 4,000 feet to last sensor

I/O Protection

Over-voltage, Miswiring, EMI/RFI Immunity

Integration Options

Remote Alarm Module (Remote Operation and 2 Alarm Relays plus Fault)
Hart Integration Module (Hart Communication Protocol version 7.0, HART Registered)
Wireless Integration Module (Detcon Model RXT-320 SmartWireless® Transceivers)

Teledyne Gas & Flame Detection quality assurance programmes demand the continuous assessment and improvement of all our products. Information in this leaflet could thus change without notification and does not constitute a product specification. For more information, please contact us or your company representative



AMERICAS
4055 Technology Forest Blvd.The
Woodlands, TX 77381
USA
Tel.: +1 713-559-9200
Fax: +1 713-893-6729

EMEA
ZI Est, Rue Orfila,
CS 20417
62027 ARRAS CEDEX, France
Tel.: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00

asia pacific
290 Guiqiao Road
Pudong, Shanghai 201206
People's Republic of China
Tel.: +86-21-3127-6373
Fax: +86-21-3127-6365