

Model IR-700-CO₂

Carbon Dioxide Sensor



Scrolling Full Message/Text Display



Non-dispersive Infrared Optical
(shown as PN 967-424520-005 in SS junction box)



Features

Failsafe User-Friendly Interface

- LED Display (With Antiglare Cover)
- Full Text Display Method
- Non-intrusive Interface
- Auto Zero/Auto Span
- Pre-emptive Fault Diagnostics

Environmentally Resistant

- Electropolished 316SS Construction
- 100% Epoxy Encapsulated Circuitry
- I/O Protection
- Water-Resistant, Corrosion-Resistant
- Vibration-Resistant

Modular and Serviceable

- Modular Design
- Plug and Play Components
- Quick Thread Release (For Sensor Replacement)
- Integral Calibration Port

Description

Model IR-700-CO₂ is a non-intrusive “Smart” sensor designed to detect and monitor carbon dioxide gas in air using miniature non-dispersive Infrared Optical (NDIR) sensor technology. Available in a low and a high range version, ranges of detection (by volume) are 0-0.3%, 0-1%, 0-3%, 0-5% (low range version) and 0-10%, 0-25%, 0-50%, and 0-100% (high range version). The plug-in, field replaceable detector provides a selective response to CO₂ and features over-sized gold-plated connections that help prevent corrosion. The Model 700’s rugged framework includes an electro-polished 316 stainless steel housing with fully encapsulated electronics and dual layer surge protection. This innovative design virtually eliminates sensor failure due to water ingress, corrosion, vibration, and transient spikes. A primary feature of the Model IR-700-CO₂ is embedded intuitive software that simplifies operator interface by guiding the user through routine calibration, configuration, and fault diagnostic functions using a built-in alpha/numeric display. The Model IR-700-CO₂ is equipped with standard analog 4-20mA, and Modbus™ RS-485 outputs. Additional integration options include a Remote Alarm Module (RAM) & HART. Detcon’s carbon dioxide gas sensor has an infinite shelf life and is supported by a 5-year pro-rated warranty.

Applications

- Chemicals
- Pesticides
- Agriculture & Horticulture
- Food & Beverage Bottling Plants
- Sewer Entry
- Waste Water Treatment Plants
- Coal Gasification
- Pulp & Paper Mills
- Enhanced Oil Recovery



Model IR-700-CO₂

Carbon Dioxide Sensor

System Specifications

Sensor Type

Continuous diffusion/adsorption
Non-dispersive Infrared Optical (NDIR) - CO₂
Sub-miniature plug-in field replaceable

Sensor Life

5 years typical

Measurement Range (% by volume)

0-0.3, 0-0.5, 0-1, 0-3, 0-5 (low range version)
0-10, 0-15, 0-20, 0-25, 0-50, 0-100 (high range version)

Accuracy/Repeatability

±5% of range

Response Time

T50 < 15 seconds, T90 < 40 seconds

Outputs

Linear 4-20 mA DC
RS-485 MODBUS-RTU

Electrical Classification

Explosion proof
cCSAus
Class I, Division 1, Groups B, C, D (Tamb = -40°C to +75°C)
Class I, Zone 1, Group IIB+H2
ATEX
II 2 G Ex d IIB + H2 T4 Gb (Tamb = -40°C to +70°C)

Ingress Protection

NEMA 4X, IP66

Safety Approvals

cCSAus
ATEX
CE Marking

Warranty

Plug-in detector - 5 year pro-rated
Transmitter - 2 Years

Environmental Specifications

Operating Temperature Range

-40°F to +167°F; -40°C to +75°C

Storage Temperature Range

-40°F to +167°F; -40°C to +75°C

Operating Humidity Range

0-100% RH non-condensing

Specifications subject to change without notice

Order Guide

Specify junction box options (below)

PN 967-405520-005	IR-700-CO2 (5% Range) Sensor Assembly (no J-Box)
PN 967-401520-005	IR-700-CO2 (5% Range) Sensor Assembly with Aluminum J-Box
PN 967-404520-005	IR-700-CO2 (5% Range) Sensor Assembly with 316 SS J-Box
PN 967-425520-025	IR-700-CO2 (25% Range) Sensor Assembly (no J-Box)
PN 967-421520-025	IR-700-CO2 (25% Range) Sensor Assembly with Aluminum J-Box
PN 967-424520-025	IR-700-CO2 (25% Range) Sensor Assembly with 316 SS J-Box

Mechanical Specifications

Dimensions

7"H x 2.2" Dia.; 178mmH x 65mm Dia. (sensor assembly only)
11"H x 6.1"W x 3.75"D; 280mmH x 155mmW x 96mmD
(with junction box)
Mounting holes (J-box) 5.5"; 140mm center to center

Weight

2 lbs; 0.907kg (sensor only)
6 lbs; 2.72kg (w/aluminum j-box)
9 lbs; 4.08kg (w/stainless steel j-box)

Electrical Specifications

Power Input

11-30 VDC

Power Consumption

Normal operation = 68mA (<1.7 watt)
Maximum = 85mA (2 watts)

Inrush Current

0.67A @ 24V

RFI/EMI Protection

Complies with EN50270

Analogue Output

Linear 4-20mA DC (1,000 ohms max loop load @ 24VDC)
0mA All Fault Diagnostics
2mA In-Calibration
4-20mA 0-100% full-scale
22mA Over-range condition

Serial RS-485 Output

RS-485 Modbus™ RTU

Baud Rate

9600 BPS (9600,N,8,1 Half Duplex)

Status Indicators

4-digit LED display with gas concentration
Full-script menu prompts for AutoSpan,
Set-up Options, and Fault Reporting

Faults Monitored

Loop, Input Voltage,
Zero, Sensor,
Processor, Memory, Calibration

Cable Requirements

Power/Analogue
3-wire shielded cable
Maximum distance is 13,300 feet with 14 AWG
Serial Output
2-wire twisted-pair shielded cable specifically for use with
RS-485 installations
Maximum distance is 4,000 feet to last sensor

I/O Protection

Over-voltage, Miswiring, EMI/RFI Immunity

Integration Options

Remote Alarm Module (Remote Operation and 2 Alarm Relays plus Fault)
Hart Integration Module (Hart Communication Protocol version 7.0, HART Registered)

Teledyne Gas & Flame Detection quality assurance programmes demand the continuous assessment and improvement of all our products. Information in this leaflet could thus change without notification and does not constitute a product specification. For more information, please contact us or your company representative



AMERICAS
4055 Technology Forest Blvd.The
Woodlands, TX 77381
USA
Tel.: +1 713-559-9200
Fax: +1 713-893-6729

EMEA
ZI Est, Rue Orfila,
CS 20417
62027 ARRAS CEDEX, France
Tel.: +33-3-21-60-80-80
Fax: +33-3-21-60-80-00

ASIA PACIFIC
290 Guiqiao Road
Pudong, Shanghai 201206
People's Republic of China
Tel.: +86-21-3127-6373
Fax: +86-21-3127-6365