

Ax60+ KIOSK

Simple safety in a box

by **ANALOX**



A wall mount, single point CO₂ monitor, **designed for kiosks.**

Carbon dioxide (CO₂) is stored and used in several industries including **beverage and hospitality, laboratory and agriculture**. CO₂ is a toxic gas and a relatively small volume can cause serious health risks if it builds up in the confines of a small space.

The Ax60+ Kiosk is a CO₂ monitor and alarm specifically designed by Analox to alert personnel to a build up/leak of CO₂ using a **state-of-the-art infrared sensor**. The alarm provides both audio and visual alerts in the case of increased levels of CO₂. **Extra alarms can be added as needed** and the unit does not need periodic calibration.


The sensor should be installed at around **450mm/18inches above the floor as CO₂ is heavier than air** and can collect at low levels. The alarm should be located either above the sensor at working head height (between 1800mm and 1950mm - 70 and 76 inches), or at the entrance to the area storing gas, to warn personnel of the CO₂ status before entering the confined space. **The alarm unit takes its power from the sensor unit which is connected to a standard electrical socket.**

Features

- Low maintenance
- Quick Connect System
- Pre-wired, ready to go
- Can support up to 4 alarm units
- Push button for unit testing

Applications

Designed specifically for Kiosks.



Gases Detected

Carbon Dioxide (CO₂)

Analox Recommends

One CO₂ alarm should be placed at working head height above the sensor and an additional CO₂ alarm can be placed at the entrance as an early warning.

Did you know...

Up to 4 CO₂ Alarms can be connected to the Ax60+ Kiosk.

Want to talk
about your
**application
requirements?**
Give us a call!

Your Challenge, **Our Passion**

Speak to **our team today** UK/Global: +44 (0)1642 711 400
US Office: (714) 891 4478
US Toll Free: (877) 723 3247

Ax60+ KIOSK



FACT

The Ax60+ Kiosk was **designed specifically with fast food kiosks in mind** as a smaller and more compatible system in the Ax60+ range.

Tech Spec

Ax60+ Kiosk Sensor	
Gas detected	Carbon Dioxide (CO ₂)
Sensor technology	Infrared
Range	0.1% to 5%
Default alarm set-points	USA regulations (NFPA 55, IFC, NBIC, OSHA and NIOSH): TWA - 5,000ppm (0.5%) AL1 - 5,000ppm (0.5%) AL2 - 15,000ppm (1.5%) AL3 - 30,000ppm (3%)
	International/European regulations (EH40) (DIN 6653-2:2015-06 compliant, assessed by TUV): TWA - 5,000ppm (0.5%) AL1 - 15,000ppm (1.5%) CO ₂ - 30,000ppm (3%)
Warm up time	40 Seconds
Resolution	0.01%
Accuracy	±2.5% of the alarm levels
Response Time	30 seconds to T90
IP Rating	IP55
LED indicators	Green = Power
Warranty	5 years for both sensor and electronics

Ax60+ Kiosk Alarm	
Strobe	White LED strobe, with an option to change to blue, red or amber filter.
Sounder	min 80 dBA @3 m (9.8 feet)
IP Rating	IP55
LED indicators	Green = Power, Amber = Fault
Cable	2m included

DIMENSIONS: CO₂ SENSOR



DIMENSIONS: ALARM



You can call us **UK/Global: +44 (0)1642 711 400**
US Office: (714) 891 4478
US Toll Free: (877) 723 3247

You can email us **info@analoxgroup.com**

Visit our website **analoxgroup.com**

Follow us on



ANALOX

Your Challenge, **Our Passion**