

Model TL105

Test Lamp For Flame Detection



General Monitors



Features & Benefits

- Rechargeable/replaceable battery extends product life
- Easy-grip handle is integral with housing
- Battery charger status indicator means easy maintenance
- Explosion-proof cast aluminum housing allows for use in Class I, Divisions 1 & 2 locations
- Microcontroller monitors all operations

Description

The TL105 is a battery operated, rechargeable test lamp specifically designed to test General Monitors' UV, UV/IR and IR flame detectors. The test lamp provides a high-energy, broadband radiation source that emits sufficient energy in both the ultraviolet and infrared spectra to activate UV and/or IR flame detectors. To simulate a fire, the test lamp automatically flashes at various selectable rates.

The TL105 is designed for use in Class I, Divisions 1 & 2, Groups C and D areas. The test lamp functions on internal nickel-metal hydride batteries which, when fully charged, allows continuous operation for at least 45 minutes. An internal circuit prevents operation when the battery charge is low.

A variety of flashing test patterns, selectable through a rotary switch, allows the test lamp to check the operation of General Monitors flame detectors, including the FL4000 series, FL3000/3100 series, Types V and VI detectors. When the specific flashing pattern for a given type of flame detector is appropriately selected, the test lamp triggers the alarm or test mode.



The Safety Company

*Because every life has a **purpose...***

Specifications	
OUTPUT SPECTRUM	Broadband emissions in UV, visible and IR spectra
CHARGING TIME	3.5 hours max.
ELECTRICAL SPECIFICATION	12 VDC 130 W max.
CHARGER INPUT	110-240VAC, 50/60 Hz@ 1.5A
CHARGER OUTPUT	24 VDC @ 2.1A
CLASSIFICATION	Class I, Division 1 & 2, Groups C & D Ex tb IIIC T110°C Db Ex d IIB + H2 T4 Gb
OPERATING TEMPERATURE RANGE	5°F to +122°F (-15°C to +50°C)
CHARGING TEMPERATURE	32°F to +104°F (0°C to +40°C)
HUMIDITY	10-90% ±3% RH, non-condensing
LENGTH	13 inches (330 mm)
DIAMETER	5 inches (127 mm)
WEIGHT	7.9 lbs (3.5 kg)
WARRANTY	Two years
APPROVALS	CSA, ATEX, IECEx, CE Marking
STANDARD CONFIGURATION	TL105-0-2 — Includes power supply adapter

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products. Specifications subject to change without notice.



ID 1466-11-MC / May 2017

© MSA 2017 Printed in U.S.A.