

# SafEye Quasar™ 900

## Open Path Combustible Gas Detector



The Quasar 900 is part of the innovative SafEye Quasar open path gas detectors series, provides continuous IR technology monitoring for combustible hydrocarbon gases at very low concentrations, up to 95% obscuration, featuring advanced long range detection at up to 660ft (200m), high-speed response in under 3 seconds.

The Quasar 900 ensures reliable and accurate protection to keep a SafEye on your safety.

# Features and benefits

- Detects combustible hydrocarbon gases, including alkanes (methane to hexane) and ethylene at up to 660 ft. (200 m).
- Accurate and reliable high-speed response in under three seconds
- Uses infrared technology
- High false alarm immunity
- Built-in event recorder - real time record of the last 100 events
- Strengthened reliability and durability with a massive three-year warranty
- Easy installation and maintenance
- Heated window for operation in harsh weather conditions (snow, ice, or condensation)
- Detection of a cloud of gas at very low concentrations, up to 95 percent obscuration
- User programmable via HART® or RS-485 Modbus® compatible with modern user interface for ease of use
- Certified performance/Hazardous Area approved (FM, ATEX, IECEx, CSA, and more) for location in Zone 1 areas and 3rd party performance approved (EN54-10, FM, DNV)
- Approved to Safety Integrity Level 2 (SIL2 - TÜV)
- High reliability-MTBF-minimum 100,000 hours

[VIEW PRODUCT >](#)

# Applications

- Offshore platforms and FPSOs
- Petrochemical plants
- Chemical
- Gas filling and distribution terminals
- Gas transport and pipelines
- Large storage areas and buildings
- Perimeter monitoring

---

## Contents

Features and benefits..... 2

Applications..... 2

Specifications..... 3

Accessories..... 5

# Specifications

## General specifications

Table 1: Detection Range

Detector model: QR	Source model: QT			
	901	902	903	904
Feet	23-66	50-132	115-330	265-660
Meters	7-20	15-40	35-100	80-200

<b>Detected gas</b>	C1-C8 selective gases
<b>Response time</b>	< 3 seconds (T90 < 10 seconds)
<b>Immunity to false alarm</b>	Not influenced by solar radiation, hydrocarbon flames, and other external infrared radiation sources
<b>Sensitivity range</b>	0-5 LEL.m methane and propane 0-8 LEL.m ethylene
<b>Displacement/misalignment tolerance</b>	±0.5 degrees
<b>Drift</b>	±7.5 percent of the reading or ±4 percent of the full scale (whichever is greater)
<b>Minimum detectable level</b>	0.15 LEL.m
<b>Temperature range</b>	-67 to +149 °F (-55 to +65 °C)
<b>Humidity</b>	Up to 95 percent non-condensing (withstands up to 100 percent relative humidity for short periods)
<b>Heated optics</b>	To eliminate condensation and icing on the window
<b>Warranty</b>	Safety system - three years

## Electrical specifications

<b>Power supply</b>	24 Vdc nominal (18-32 Vdc)
<b>Power consumption (peak includes heated optics)</b>	Detector: 250 mA (300 mA peak) Source: 250 mA (300 mA peak)
<b>Warm-up time</b>	30 seconds for transmitter and receiver
<b>Electrical connection (specify)</b>	Two ¾-in. - 14 national pipe thread (NPT) conduits or 2 x M25 x 1.5 mm ISO
<b>Electrical input protection</b>	Per MIL-STD-1275B
<b>Electromagnetic compatibility</b>	Electromagnetic interference/radio frequency interference (EMI/RFI) protected per EN50270

## Outputs-interfaces

<b>0-20 mA current output</b>	Sink (source option) configuration: maximum load of 500 ohm at 18-32 Vdc Gas reading: 4-20 mA Normal, zero reading: 4 mA Maintenance call: 3 mA Obscuration/beam block: 2 mA
-------------------------------	--

	Zero calibration mode: 1 mA Fault: 0 mA
<b>RS-485 interface-Modbus® compatible</b>	The RS-485 input/output provides complete data information to a PC and receives control commands from the PC or handheld unit.
<b>HART®</b>	HART communication on 0-20 mA analog (FSK) - used for maintenance and asset management
<b>Visual status indicator</b>	Three color light-emitting diode (LED) <ul style="list-style-type: none"> <li>■ Green: power on</li> <li>■ Yellow: fault</li> <li>■ Red: alarm</li> </ul>

### Mechanical specifications

<b>Enclosure</b>	The source and detector housings are stainless steel 316L with electro polish finish. The circuit boards are conformal coated and protected from mechanical vibrations. The tilt mount is also stainless steel 316L.
<b>Dimensions</b>	Detector/source: 10.5 x 5.1 x 5.1 in. (267 x 130 x 130 mm) Tilt mount: 4.7 x 4.7 x 5.5 in. (120 x 120 x 158 mm)
<b>Weight</b>	Detector/source: 11 lb. (5 kg) Tilt mount: 4.2 lb. (1.9 kg)
<b>Water and dust tight</b>	IP66 and IP68 NEMA 250 6P
<b>Environmental</b>	Meets MIL-STD-810C for humidity, salt and fog, vibration, mechanical shock, and high and low temperature

### Approvals

Table 2: Hazardous Area

ATEX and IECEx	Ex II 2 (2)G D Ex db eb ib [ib Gb] IIB + H2 T4 Gb Ex tb IIIC T135 °C Db Ta = -55 °C to +65 °C
FM/FMC	Class I Div 1 Groups B, C, and D Class II, III Div 1 Groups E, F, and G
TR CU (EAC)	1Ex d e ib [ib Gb] IIB + H2 T4 Gb X Ex tb IIIC T135 °C Db X
Inmetro	Ex db eb ib [ib Gb] IIB + H2 T4 Gb Ex tb IIIC T135 °C Db

<b>Performance</b>	Approved per FM6325 and tested by FM per EN60079-29-4
<b>Reliability</b>	SIL2 per IEC61508 (TUV)

## Accessories

Part number	Description
888270	Tilt mount
799255	Wall mount
799225	U-bolt/pole mount: 4 to 5 in. (101.6 to 127 mm)
888140	U-bolt/pole mount: 2 to 3 in. (50.8 to 76.2 mm)
888247-1	Methane commissioning kit, spare kit
888247-2	Propane commissioning kit, spare kit
888247-3	Ethylene commissioning kit, spare kit
888810	HART® handheld diagnostic unit
888815	HART harness kit
794079	USB/RS485 harness converter kit
888263	Weather cover
888335-2	Duct mount







For pricing or further information, please contact us using the details below

### **Cadmus Products**

**Tel: +44 (0)330 088 0595**

**Email: [info@cadmus.co.uk](mailto:info@cadmus.co.uk)**

**Website: [www.cadmus.co.uk](http://www.cadmus.co.uk)**

Please note - Product designs and specifications are subject to change without notice.  
The user is responsible for determining the suitability of this product.

[About Us](#)

[Shipping](#)

[Terms & Conditions](#)

[Privacy Policy](#)

[Brands](#)

