

## MODEL S4100T H2S SMART TRANSMITTER



S4100T - 1 5 - 0 - 1

### TRANSMITTER:

(Std) HYDROGEN SULPHIDE SMART TRANSMITTER

### A. H2S-SENSOR:

- |                                    |   |
|------------------------------------|---|
| 00- <input type="checkbox"/>       | NONE  |
| 99- <input type="checkbox"/>       | REMOTE ONLY NO SENSOR REQUIRED                    |
| 11- <input type="checkbox"/>       | 51457-1 SENSOR STAINLESS STEEL ATEX H2S 0-100 ppm |
| 13- <input type="checkbox"/>       | 51457-5 SENSOR STAINLESS STEEL ATEX H2S 0-50 ppm  |
| 15- <input type="checkbox"/> (Std) | 51457-9 SENSOR STAINLESS STEEL ATEX H2S 0-20 ppm  |

### B. H2S-HOUSING:

- |                                   |   |
|-----------------------------------|---|
| 0- <input type="checkbox"/> (Std) | NONE                                    |
| 1- <input type="checkbox"/>       | B14-020-1 POLYESTER HOUSING, 20mm, ATEX |
| 2- <input type="checkbox"/>       | B14-020-2POLYESTER HOUSING, 20mm, GOST  |

### C. APPROVALS/LANGUAGE:

- |                                   |                             |
|-----------------------------------|-----------------------------|
| 1- <input type="checkbox"/> (Std) | ATEX/ENGLISH                |
| 2- <input type="checkbox"/>       | ATEX/FRENCH                 |
| 5- <input type="checkbox"/>       | RUSSIAN W/RUSSIAN NAMEPLATE |
| 6- <input type="checkbox"/>       | ATEX & BV/ENGLISH           |
| 7- <input type="checkbox"/>       | ATEX & BV/FRENCH            |

### NOTES:

1. Detection range is field selectable.
2. Correct sensor must be fitted if changing range.