

MODEL S4100C HYDROCARBON GAS TRANSMITTER



S4100C- 1 2 - 0 - 1 - 1

HYDROCARBON SMART TRANSMITTER:

(Std) S4100C Hydrocarbon Smart Transmitter

A. COMBUSTIBLE-SENSOR:

- | | |
|------------------------------------|--|
| 00- <input type="checkbox"/> | NO SENSOR (SENSOR STOPPING PLUG NOT PROVIDED) |
| 99- <input type="checkbox"/> | REMOTE ONLY, NO SENSOR REQUIRED |
| 12- <input type="checkbox"/> (Std) | 11159-1 SENSOR STAINLESS STEEL STANDARD INDUSTRIAL HC ATEX |
| 14- <input type="checkbox"/> | 11159-2 SENSOR STAINLESS STEEL HI-TEMP HC ATEX |

B. COMBUSTIBLE-HOUSING:

- | | |
|-----------------------------------|---|
| 0- <input type="checkbox"/> (Std) | NONE |
| 1- <input type="checkbox"/> | B13-020-1 ATEX POLYESTER HOUSING, 20 mm, TEMP 75C |
| 2- <input type="checkbox"/> | B13-021-1 ATEX HI TEMP HOUSING, 20 mm, 180C |
| 3- <input type="checkbox"/> | B13-020-2 GOST POLYESTER HOUSING, 20 mm, TEMP 75C |
| 4- <input type="checkbox"/> | B13-021-3 GOST HI TEMP HOUSING, 20 mm, 180C |

C. APPROVALS/LANGUAGE:

- | | |
|-----------------------------------|--------------------------------|
| 1- <input type="checkbox"/> (Std) | ATEX/ENGLISH |
| 2- <input type="checkbox"/> | ATEX/FRENCH |
| 3- <input type="checkbox"/> | ATEX/GERMAN |
| 4- <input type="checkbox"/> | ATEX/ITALIAN |
| 5- <input type="checkbox"/> | RUSSIAN WITH RUSSIAN NAMEPLATE |
| 6- <input type="checkbox"/> | ATEX & BV/ENGLISH |
| 7- <input type="checkbox"/> | ATEX & BV/FRENCH |
| 8- <input type="checkbox"/> | ATEX & BV/ITALIAN |

D. CABLE ENTRY:

- | | |
|-----------------------------------|-------------------------|
| 1- <input type="checkbox"/> (Std) | 2 X 20 mm CABLE ENTRIES |
|-----------------------------------|-------------------------|

NOTES:

1. If sensor 11159-2 is selected, housing type B13-021-1 (or B13-021-3) is required.