Euro Price List Effective 01 Jan 2016



by MSA

MODEL FL3111 UV FLAME DETECTOR

A B C D E

FL3111 - 1 - 5 - 1 - 3 - 1

FLAME DETECTOR:

(Std) UV FLAME DETECTOR, Stainless Steel

A. OUTPUT-OPTIONS:

1- □ (Std) 0-20mA ONLY 2- □ RELAYS X3

 $\begin{array}{lll} \text{3-} & \square & \text{RELAYS } \text{X2} + \text{END OF LINE RESISTOR} \\ \text{4-} & \text{0-20mA} + \text{SINGLE COMMS} \end{array}$

5- □ DUAL COMMS

B. RELAY-STATE-NC:

1- □ LATCH ALARM/NON-LATCH WARN DE-ENERGIZED
2- □ LATCH ALARM/NON-LATCH WARN ENERGIZED
3- □ LATCH ALARM/LATCH WARN DE-ENERGIZED
4- □ LATCH ALARM/LATCH WARN ENERGIZED
5- □ (Std) NON-LATCH ALARM/NON-LATCH WARN DE-ENERGIZED
6- □ NON-LATCH ALARM/NON-LATCH WARN ENERGIZED
7- □ NON-LATCH ALARM/LATCH WARN DE-ENERGIZED
8- □ NON-LATCH ALARM/LATCH WARN ENERGIZED

C. SENSITIVITY:

1- □ (Std) 100% SENSITIVITY 2- □ 75% SENSITIVITY 3- □ 50% SENSITIVITY

D. TIME-DELAY:

2- □ 2 SECOND DELAY 3- □ (Std) 4 SECOND DELAY 4- □ 8 SECOND DELAY 5- □ 10 SECOND DELAY

E. APPROVALS/LANGUAGE:

1- □ (Std) ATEX/ENGLISH

2-
RUSSIAN W/RUSSIAN NAMEPLATE

Notes

1. Mounting bracket is included in the basic price

1-4