

**HORIBA**  
Scientific

# LAQUA

LAQUA PH1500 Benchtop Water Quality Meter



pH

ORP

Temperature



[www.horiba-laqua.com](http://www.horiba-laqua.com)



# LAQUA

LAQUA PH1500 Benchtop Water Quality Meter

Ideal for student training and routine applications.

Good value for money: no fancy bells and whistles which sounds good but are rarely used.

From a reputed manufacturer—one whose company was started with pH meters back in 1945.


## USA, NIST, & DIN pH Buffer Groups

More pH buffer options for calibration



## Visual Electrode Status Indicator

Shows electrode condition after calibration



## Universal Power Adaptor

Multi-voltage (100-240V) and 6 plugs (US, UK, EU, ANZ, Korea, China) included


## Data Output to Printer Capability

Print data using RS232 cable and printer



## pH & ORP Measurement Modes with ATC

Accurate measurements with the meter and 3-in-1 pH and ORP electrodes



## Adjustable, Integrated Electrode Stand

Holds up to 2 electrodes and can be positioned on either side of the meter



## Smaller Footprint

Occupies minimal space on lab desk



## Offset & Average Slope

Viewable pH calibration data



## Up to 5 pH Calibration Points

6 points for DIN Buffer Group



Ready to go out of the box

Meter kits come with a 3-in-1 pH electrode, electrode fill solution, and pH buffers


## Data Acquisition Software Connectivity

Export data to computer using USB cable and software



## Large Memory

Up to 1000 data sets




## Auto Data Log

Efficiently capture and save data into internal memory



## Auto Stable, Auto Hold and Real Time Measurement Modes

Smiley face and HOLD icons serve as reading stability indicators



## Meter Specifications



| LAQUA PH1500<br>pH/ORP/Temp (°C/°F) Bench Meter |   |
|---|---|
| pH Range  | -2.00 to 16.00 pH                                       |
| Resolution                                      | 0.01 pH   |
| Accuracy  | ± 0.01 pH   |
| pH Buffer Groups                                | USA, NIST, DIN  |
| Calibration Points                              | Up to 5 (USA, NIST) / Up to 6 (DIN)                     |
| ORP Range                                       | ± 2000.0 mV   |
| Resolution                                      | 0.1 mV (< ±1000 mV), 1 mV (≥ ±1000mV)                   |
| Accuracy  | ±0.3 mV (< ±1000 mV), 0.3% of reading (≥ ±1000mV)       |
| Calibration Option                              | Yes (Up to ±200 mV)                                     |
| Temperature Range                               | -30.0 to 130.0 °C / -22.0 to 266.0 °F                   |
| Resolution                                      | 0.1 °C / °F   |
| Accuracy  | ± 0.5 °C / ± 0.9 °F                                     |
| Calibration Option                              | Yes ( ± 10.0 °C / ± 18.0 °F range in 0.1 °C increments) |
| Memory  | 1000 data sets  |
| Auto Data Log                                   | Yes   |
| Measurement Modes                               | Auto Stable / Auto Hold / Real Time                     |
| Offset & Slope Display                          | Yes (Average slope)                                     |
| Auto Shut-Off                                   | Yes (programmable: 1 to 30 mins.)                       |
| Electrode Status                                | On screen display                                       |
| PC Communication                                | Yes   |
| Printer Communication                           | Yes   |
| Meter Inputs                                    | BNC, phono (ATC), DC sockets                            |
| Communication                                   | Phono jack (USB / RS232)                                |
| Display   | Static segment LCD with 160 segments                    |
| Power Requirement                               | AC adaptor 100 ~ 240V, 50-60Hz                          |
| Dimensions (LxWxH mm)                           | 155x150x67 (meter) / 410x260x230 (boxed)                |
| Weight  | 720g (meter only) / 3700g (complete set)                |
| Electrode Stand                                 | Integrated  |
| Warranty  | Meter 3 years, electrode 6 months                       |

## Ordering Information

| Meter Kits   |  |
|--|--|
| PH1500<br>3200875198                               | <ul style="list-style-type: none"> <li>Meter with integrated electrode stand</li> <li>Universal power adaptor with 6 plugs</li> <li>Manual</li> </ul>  |
| PH1500-SS  | <ul style="list-style-type: none"> <li>PH1500 with integrated electrode stand</li> <li>9651-10D sealed, plastic body pH electrode</li> <li>pH 4, 7 and 10 buffer solutions &amp; 3.33M KCl (250ml each)</li> </ul>     |
| PH1500-SR  | <ul style="list-style-type: none"> <li>PH1500 with integrated electrode stand</li> <li>9625-10D refillable, plastic body pH electrode</li> <li>pH 4, 7 and 10 buffer solutions &amp; 3.33M KCl (250ml each)</li> </ul> |
| Electrodes   |  |
| 9651-10D<br>3200642020                             | Plastic-body, sealed Gel-filled pH electrode with integrated temperature sensor  |
| 9625-10D<br>3200360505                             | Plastic-body, refillable Gel-filled pH electrode with integrated temperature sensor  |
| pH Buffers   |  |
| 250-PH-4<br>250-PH-7<br>250-PH-10                  | USA buffers pH 4,01, 7,00 and 10,01 buffer solution, 250 ml in dosing bottle, NIST Traceable with certificate, accuracy ± 0,01 @ 25°C  |
| 101-S<br>3200043642                                | NIST buffers solution kit with pH6,86 (500ml), 4,01 and 9,18 (250ml) & 3.33 KCl Internal Solution (250ml) with dropper   |
| Accessories  |  |
| Printer<br>3014030147 (230V),<br>3014030146 (120V) | Comes with plain paper; printer cable is sold separately   |
| Printer (RS232) Cable<br>3200779638                | 1.5 m length; connects meter and printer   |
| PC (USB) Cable<br>3200779639                       | 1.5 m length; connects meter and computer; comes with free data acquisition software   |
| Printer Paper<br>3014030149                        | 20 rolls   |
| Ink Ribbon<br>3014030150                           | 5 pcs/set  |


**Water Quality Analyzers**

With over 75 years of engineering excellence, HORIBA's diverse range of water quality analyzers and electrodes are ideal for everyday laboratory needs through to the most demanding of applications. Visit our website for a wealth of useful information and water quality measurement tips to help you obtain the best results in your work.



**Benchtop Meters**

Developed using extensive feedback from users, our new LAQUA meters deliver the best solution for water quality analysis. Our LAQUA website features an online 'Selection Guide' to enable you to find the perfect LAQUA meter and electrode for your need.



**Handheld Meters**

In the lab, in the field or anywhere you need it. LAQUA Handheld meters are designed for use with one hand and with an IP67 waterproof rating and shock-resistant casing. Meters can be used for long periods, even in dark places, making it ideal for field measurements in rivers and lakes.



**Electrodes**

Various electrodes to match any application. A wide range of products for both benchtop and portable systems are available, including easy and reliable standard models, application-focused models for small samples or large containers, and special electrodes for specific sample characteristics.



**Pocket Meters**

Analyzing water quality is simplified when using our LAQUAtwin range of meters. Designed to produce accurate and reliable results. Anyone, anywhere, at any time can measure samples easily with a LAQUAtwin meter. See just how good they are at our website.



**Application Notes**

LAQUAtwin pocket meters offer quick and convenient alternative to analyze important parameters with high accuracy. Several application notes are available at (<http://goo.gl/znwE6j>) detailing the use of LAQUAtwin and the results achieved for the respective applications. Additional application notes will be added when available.



Visit the **HORIBA UK** Channel on YouTube and subscribe to see more of our videos.



**RoHS**

**UK CA**

- The contents of this catalog are subject to change without prior notice, and without any subsequent liability to this company.
- The color of the actual products may differ from the color pictured in this catalog due to printing limitations.
- It is strictly forbidden to copy the content of this catalog in part or in full.
- All brand names, product names and service names in this catalog are trademarks or registered trademarks of their respective companies.
- Windows is a registered trademark of Microsoft Corporation in the United States and other countries.

