TELEDYNE GAS MEASUREMENT INSTRUMENTS Everywhereyoulook[™]

PS500 - CO2

The Carbon Dioxide detection solution



Auto Bump & Calibration Station

- Simple user interface
- Bump test or calibration
- Bump/calibration results storage
- Standalone, PC or Ethernet options
- Robust construction

Designed by our customers, this robust and accurate gas detector provides unrivalled protection in confined space applications.

- 0-5% Carbon Dioxide (CO2) detection
- NDIR sensing technology
- Large font for easy reading
- Piercing 95 dB audible plus 360-degree high-visibility light bar
- On-board datalogging for calibration certificates, data management, and event logging
- High impact rubberised case
- IP65
- Low cost of ownership





The Carbon Dioxide detection solution



The PS500- CO2 detects 0-5% volume CO2 reliably and accurately using infrared capabilities.

The large display font allows for easy measurement readings.

The PS500-CO2 is particularly useful in noisy environments, featuring a very loud (95dBA) penetrating and distinctive audible alarm together with high visibility large area visual alarm.

Sampling type: diffusion for confined space working.

A robust moulded, rubberised casing guranteeing Hi-impact resistance, the PS500-CO2 can be used in the most demanding industrial environments.

	Technical specification		Sensor specification				
Size	140 x 85 x 45 mm / 5.5" x 3.3" x 1.7"	Gas	Range	Resolution	Sensor type	T90	
Weight:	0.4 kg / 14 oz.		0 - 2.50%	0.01%			
Humidity:	0-98% non condensing	CO ₂	2.50 - 5.00%	0.05%	NDIR	25 s	
Alarms:	Visual 360° full light bar, piercing 95db audible 4 gas alarms per gas user programmable TWA/STEL alarms visual and audible Flow fault visual and audible Low battery alarm	61371 P					
Display:	LCD backlight display		The instrument is supplied calibrated and complete with: - Charger (Universal plug) - Battery / sensor grille key - User CD				
Datalogging:	Timed: 24 hours of timed logs at 1 log per minute Session: Minimum of 180 logs Calibration: Minimum of 8 calibration logs						
Battery:	NiMH rechargeable battery–12 hr. minimum		- Quick operation gui	de			
Enclosure:	High impact rubberised polycarbonate case	66028	Neck harness				
Rating:	IP65 (Dust tight and water resistant)	61208	Datalogging package				
Approvals:	CE 0518	66083	Sensor grill hydrophobic filter				
	ATEX $\langle \mathbf{E}_{\mathbf{x}} \rangle$ II 2 G EEx iad IIC T3	66084	Sensor gas inlet filter				
ECEx:	EEx iad IIC T3	66206	Car/vehicle charge 12/24V				
Warranty:	2 years	61502	Automatic Bump / Co	alibration Station			

As an ISO 9001 approved company, Gas Measurement Instruments quality assurance programes demand the continuous assessment and improvement of all GMI products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representative if you require more details.



Copyright © 2020 Teledyne Technologies. GF-00260D-EN . All rights reserved, gasandflamedetection@teledyne.com